

## Electrolux Dryers for OPL

### 30x30, 45x45 stack, 30, 60, 77, 100, & 135 lb. capacities

#### High performance combined with significant energy savings.

Built to last, Electrolux dryers are precision-engineered for efficiency, ease of use, and superior drying results. Perfect for hotels, motels, hospitals, nursing homes, gyms, salons, schools, and other facilities. You'll appreciate the "green" engineering, easy operation, and years of low maintenance.

#### Features and benefits:

- Increase your productivity per square foot with new Electrolux stack dryers.
- Optimal combination of gas consumption (Btu/hr) and airflow (CFM) provides the fastest drying with lowest energy consumption.
- Extra large doors make loading and unloading easy.
- Self-cleaning lint screen and large lint compartment for easy maintenance.
- Quiet operation. Designed to keep noise level below 70 dB (A).

#### Designed with you in mind:

- Reversing drum (standard) minimizes tangling and wrinkling. Improves dryer efficiency and makes flatwork finishing easier.
- Fresh air intake adapter acquires air from a location outside the dryer area. Useful when dryers are installed in interior or air-conditioned space.

#### Residual Moisture Control:

The Residual Moisture Control (RMC) option is available in all Electrolux single pocket dryers. RMC prevents damage to garments caused by overdrying and reduces lint and wrinkles by automatically stopping the dryer when the exact pre-set moisture level is reached. The amount of residual moisture in the fabric is important for proper finishing. If the load is to be further processed by an ironer, RMC will shut the dryer off while there is still sufficient moisture for the ironer to work effectively. By not overdrying, you'll benefit from longer linen life and significant labor and energy savings.



30x30, 45x45, 30, 60, 77, 100, and 135 lb. capacities.  
Available in stainless or wave front panel.

### The future of professional laundry is here.

With more than 100 years of experience designing professional laundry equipment, Electrolux is dedicated to providing you with precision-engineered washers, dryers, and flatwork ironers. Products are certified in accordance with ISO 9001 and ISO 14001 standards, guaranteeing Electrolux Professional's long-term commitment to quality and the environment.

Take control of your laundry operations with Electrolux Professional Laundry.

Share more of our thinking at [www.electroluxusa.com/laundrysystems](http://www.electroluxusa.com/laundrysystems)

| Model   | T4300            |          | T4290    |         | T4530    |         | T4650     |         | T4900                |         | T41200               |         |
|---|------------------|----------|----------|---------|----------|---------|-----------|---------|----------------------|---------|----------------------|---------|
| Capacity (lb/kg)  | 2 x 30           | 2 x 13.5 | 30       | 13.5    | 60       | 27      | 77        | 35      | 100                  | 45      | 135                  | 65      |
| Width (in/mm)   | 31 1/8           | 790      | 27 15/16 | 710     | 37 13/16 | 960     | 37 13/16  | 960     | 50 13/16             | 1290    | 50 13/16             | 1290    |
| Depth (in/mm)   | 43 11/16         | 1110     | 44       | 1120    | 46 7/16  | 1180    | 53 15/16  | 1370    | 51                   | 1295    | 58 7/16              | 1485    |
| Depth with door open (in/mm)  | 72 7/16          | 1840     | 71 1/4   | 1810    | 83 7/16  | 2120    | 90 9/16   | 2300    | 94 1/2               | 2400    | 101 15/16            | 2590    |
| Height Overall (in/mm)  | 76 3/8           | 1940     | 74       | 1880    | 78 9/16  | 1995    | 78 9/16   | 1995    | 97 1/16              | 2465    | 97 1/16              | 2465    |
| Height without heating unit (in/mm)   | n/a              |          | n/a      |         | n/a      |         | n/a       |         | 77 3/8               | 1965    | 77 3/8               | 1965    |
| Door opening diameter (in/mm)   | 22 7/8           | 580      | 22 7/8   | 580     | 31 7/8   | 810     | 31 7/8    | 810     | 37                   | 940     | 37                   | 940     |
| Cylinder volume (ft <sup>3</sup> /l)  | 10.6             | 300      | 10.1     | 286     | 18.6     | 527     | 23        | 651     | 31.8                 | 900     | 42.4                 | 1200    |
| Crated Weight (lb/kg)   | 693              | 315      | 539      | 245     | 781      | 355     | 792       | 360     | 1100                 | 500     | 1166                 | 530     |
| <b>Utility Connections</b>  |                  |          |          |         |          |         |           |         |                      |         |                      |         |
| Exhaust duct diameter (in/mm)   | 8                | 200      | 8        | 200     | 8        | 200     | 8         | 200     | 12                   | 315     | 12                   | 315     |
| Gas connection  | 1/2 NPT          |          | 1/2 NPT  |         | 1/2 NPT  |         | 3/4 NPT   |         | 1 NPT                |         | 1 NPT                |         |
| Steam connection, inlet & condensate  | n/a              |          | 1/2 NPT  |         | 3/4 NPT  |         | 3/4 NPT   |         | 1 NPT                |         | 1 NPT                |         |
| <b>Energy Data</b>  |                  |          |          |         |          |         |           |         |                      |         |                      |         |
| Gas (Btu/hr)  | 2 x 71,700       |          | 71,700   |         | 136,400  |         | 151,200   |         | 219,000              |         | 280,000              |         |
| Airflow (ft <sup>3</sup> /min / m <sup>3</sup> /hr) (gas heat)                                  | 2 x 354          | 2 x 600  | 406      | 690     | 683      | 1160    | 647       | 1100    | 1354                 | 2300    | 1765                 | 3000    |
| Electric (kW) @ 208-240V/3Ø   | 2 x 18           |          | 18       |         | 30       |         | 30        |         | 60                   |         | 72                   |         |
| Airflow (ft <sup>3</sup> /min / m <sup>3</sup> /hr) (elec. heat)                                | 2 x 354          | 2 x 600  | 406      | 690     | 624      | 1060    | 647       | 1100    | 1354                 | 2300    | 1765                 | 3000    |
| Steam (lb/hr /kg/hr) (approximate)  | n/a              |          | 119      | 65      | 190      | 86      | 190       | 86      | 315                  | 143     | 315                  | 143     |
| Airflow (ft <sup>3</sup> /min / m <sup>3</sup> /hr) (steam heat)                                | n/a              |          | 544      | 924     | 812      | 1380    | 647       | 1100    | 1354                 | 2300    | 1765                 | 3000    |
| <b>Electrical Requirements</b>  |                  |          |          |         |          |         |           |         |                      |         |                      |         |
| Current, gas or steam, 120 V/60Hz (full load/circuit breaker)                                   | 2 x 9 / 2 x 15   |          | 5.8 / 15 |         | 8.3 / 15 |         | 16.5 / 20 |         | n/a                  |         | n/a                  |         |
| Current, gas or steam, 208-240 V/60Hz/1Ø (full load/circuit breaker)                            | 2 x 4.5 / 2 x 15 |          | 3.4 / 15 |         | 4.2 / 15 |         | 8.3 / 15  |         | n/a                  |         | n/a                  |         |
| Current, gas or steam, 208-240 V/60Hz/3Ø (full load/circuit breaker)                            | n/a              |          | 4.1 / 15 |         | 3.8 / 15 |         | 4.8 / 15  |         | 10 / 15              |         | 10 / 15              |         |
| Current, electric, 208-240 V/60Hz/3Ø (full load/circuit breaker)                                | 2 x 50 / 2 x 65  |          | 50 / 65  |         | 80 / 100 |         | 89 / 125  |         | 75 / 100 @ 480 Volts |         | 90 / 125 @ 480 Volts |         |
| <b>Alternate Voltages</b>   |                  |          |          |         |          |         |           |         |                      |         |                      |         |
| Alternate voltages available. Contact Electrolux Professional Sales Department for information. |                  |          |          |         |          |         |           |         |                      |         |                      |         |
| <b>Supply Pressures</b>   |                  |          |          |         |          |         |           |         |                      |         |                      |         |
| Natural Gas (inches H <sub>2</sub> O/mbar)  | 6 - 10           | 15 - 25  | 6 - 10   | 15 - 25 | 6 - 10   | 15 - 25 | 6 - 10    | 15 - 25 | 6 - 10               | 15 - 25 | 6 - 10               | 15 - 25 |
| Propane (inches H <sub>2</sub> O/mbar)  | 10 - 13          | 25 - 30  | 10 - 13  | 25 - 30 | 10 - 13  | 25 - 30 | 10 - 13   | 25 - 30 | 10 - 13              | 25 - 30 | 10 - 13              | 25 - 30 |
| Steam (psi/mbar) (max)  | n/a              |          | 102      | 7       | 15 - 102 | 1 - 7   | 15 - 102  | 1 - 7   | 15 - 102             | 1 - 7   | 15 - 102             | 1 - 7   |
| Exhaust (inches H <sub>2</sub> O/mbar) (max)  | 1.57             | 3.9      | 0.32     | 0.8     | 0.23     | 0.6     | 1.30      | 3.2     | 0.37                 | 1       | 0.37                 | 1       |

**Please call for spec sheet on our T4420S stack dryer available 120 volt, single phase.**

*Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, inverse-time, common-trip, industrial-type circuit breakers ONLY. Warranty void if not properly installed. Advise when placing order if dryers are for installation at altitudes in excess of 1000 feet above sea level, as this may require a gas-orifice change. Contact Electrolux/Bermil for more information and availability of machines for electric services not listed. Specifications subject to change without notice. Electrolux/Bermil assumes no responsibility for errors or omissions in this information.*

## ELECTROLUX DRYER CONTROL

Our Selecta II control provides perfect results every time.



### Selecta II OPL

- Precise control of temperature, program, time, reversing and cool-down selection.
- Displays selected program, remaining drying time, cool-down time and actual temperature.
- With optional Residual Moisture Control (RMC), displays moisture content as well.
- Comprehensive diagnostics and service functions.



Call today for information on the full line of Electrolux Professional washers, dryers, ironers, and low-cost financing & leasing.



800.381.7222 • [www.electroluxusa.com/laundrysystems](http://www.electroluxusa.com/laundrysystems)

Bermil Industries Corp. • 461 Doughty Blvd., Inwood, NY 11096-0338  
 Sales and Administration – Tel: 516-371-4400 • Fax: 516-371-4204 • e-mail: [sales@wascomat.com](mailto:sales@wascomat.com)  
 Spare Parts – Tel: 516-371-2000 • Fax: 516-371-4029 • e-mail: [parts@wascomat.com](mailto:parts@wascomat.com)  
 Technical Support – Tel: 516-371-0700 • Fax: 516-371-4029 • e-mail: [service@wascomat.com](mailto:service@wascomat.com)  
 En Mexico: Llame gratis a este numero 001-800-010-1010  
[www.electroluxusa.com/laundrysystems](http://www.electroluxusa.com/laundrysystems)

Your local independent authorized dealer