

# Wascomat Super 200 G-Force Washers for OPL

**High-speed extraction Compass Control washers save time, water, and energy.**

Built to last, Wascomat's 200 G-Force solid-mount washers spin faster and remove more water. This results in less drying time and significant labor and energy savings. Hotels, motels, hospitals, nursing homes, restaurants, and other facilities can go right to flat-work finishing equipment after conditioning items in the dryer. You'll get superior results while saving time and money!



*Available in 20, 25, 30, 40, 55 and 75 lb. capacities. Stainless or white.*

## Dramatically different.

- Lowest water consumption in the industry.
- Installs on regular concrete pad or steel base.
- Single phase 120 or 220 volt electrical service reduces installation costs.
- Inverter driven motor for smooth operation and high efficiency.
- New soft-grip, slip-lock door handle for safe and trouble-free operation.
- Door unlocks immediately at the end of wash cycle.
- Unique 4-compartment supply dispenser lets you conveniently load all laundry supplies before starting the wash.
- Provisions to connect up to 5 liquid supplies.
- Specialty programs easily created in Wash Program Manager.
- Unibody construction eliminates welds for superior strength and durability.
- Interchangeable parts from one machine size to another.

## Features of Compass Control

- Customize wash programs to increase efficiency and reduce costs.
- Choose your display language.
- Total of 30 built in programs with room for 10 additional custom programs.
- Reduce operator error by allowing access only to the programs you use.
- Built-in diagnostics and statistics.



*Compass Control puts you in charge of your laundry operations. One knob does it all!*

## Environmentally responsible.

Wascomat equipment is accredited according to the ISO14001 Environmental Management System and ISO9001 Quality Management System. With more than a century of experience, Wascomat's state-of-the-art products are engineered for quality, energy savings, and water efficiency.

We optimize your results while lowering your operating costs and environmental impact.

**Wascomat** Laundry Equipment

1-800-645-2204 • [www.wascomat.com](http://www.wascomat.com)

*Wascomat — when laundry means business.*

Wascomat 200G SU Models	SU620		SU625		SU630		SU640		SU655		SU675	
Capacity (lb/kg)	20	8.5	25	11	30	14	40	18	55	25	75	34
Width (in/mm)	26	660	28 3/8	720	28 3/8	720	29 1/2	750	32 11/16	830	35 13/16	910
Depth (overall) (in/mm)	30 1/8	765	29 1/8	740	32 1/2	825	36	915	39	990	42 5/16	1075
Height (in/mm)	43 7/8	1115	47 1/4	1200	47 1/4	1200	52 3/16	1325	55 1/2	1410	56 7/8	1445
Height to bottom of door (in/mm)	14	355	14 3/8	365	14 3/8	365	17 1/8	435	18 1/2	470	19 11/16	500
Door opening diameter (in/mm)	12 3/16	310	14 3/8	365	15 9/16	395	15 9/16	395	17 1/8	435	17 1/8	435
Cylinder volume (ft <sup>3</sup> /l)	3.0	85	3.7	105	4.6	130	6.4	180	8.8	250	11.7	330
Cylinder diameter (in/mm)	20 1/2	520	23 7/16	595	23 7/16	595	25 9/16	650	28 9/16	725	31 5/16	795
Drain outlet diameter (in/mm)	3	75	3	75	3	75	3	75	3	75	3	75
Height to centerline of drain (in/mm)	3 15/16	100	3 15/16	100	3 15/16	100	3 15/16	100	3 15/16	100	3 15/16	100
Height to electrical connection (in/mm)	32 1/2	825	35 13/16	910	35 13/16	910	40 3/4	1035	44 1/8	1120	45 1/2	1155
Height to water connections (in/mm) (approx)	40 9/16	1030	43 7/8	1115	43 7/8	1115	49	1245	52 3/8	1330	53 3/4	1365
Dynamic load (lb/kN)	382+/-742	1.7+/-3.3	472+/-899	2.1+/-4.0	517+/-1057	2.3+/-4.7	607+/-1326	2.7+/-5.9	832+/-1664	3.7+/-7.4	994+/-1978	4.2+/-8.8
Dynamic frequency (Hz)	11.6		10.8		10.8		10.3		9.8		9.4	
Noise level (dBA)	66		71		71		76		79		77	
Net wt (lb/kg)	297	135	385	175	385	175	502	228	631	287	656	298
Crated weight (lb/kg)	343	156	431	196	431	196	528	240	664	302	700	318
<b>Operating Speeds</b>												
Wash (rpm)	52		46		46		44		42		40	
Extract (rpm/G-Force)	830 / 200		776 / 200		776 / 200		742 / 200		702 / 200		671 / 200	
<b>Electrical Requirements (standard)</b>												
Voltage/frequency/phase	208-240/60/1		208-240/60/1		208-240/60/1		208-240/60/1		208-240/60/1		208-240/60/1	
Full-load current (Amps) / Ckt breaker (Amps)	3.5 / 15		3.8/15		3.8 / 15		5 / 15		6.9 / 15		9 / 15	
Voltage/frequency/phase	120/60/1		120/60/1		120/60/1		120/60/1		120/60/1		-	
Full-load current (Amps) / Ckt breaker (Amps)	7 / 15		7.6 / 15		7.6 / 15		9.5 / 15		13.2 / 20		-	
<b>Water Information</b>												
Inlet fittings (* = 3 inlets)	3/4	DN20	3/4	DN20	3/4	DN20	3/4*	DN20*	3/4*	DN20*	3/4*	DN20*
Flow (gpm/lpm @ 45 psi) (each inlet)	5	20	5	20	5	20	5	20	16	60	16	60
Recommended water pressure (psi/kPa)	30-90	200-600	30-90	200-600	20-60	150-400	20-60	150-400	20-60	150-400	20-60	150-400

Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, common-trip, circuit breakers ONLY. Warranty void if not properly installed. Solid-mount machines require a custom concrete foundation, and are not suitable for upper-floor or above-basement installations. Contact Wascomat for more information and for availability of machines for electric services not listed. Specifications subject to change without notice. Wascomat assumes no responsibility for errors or omissions in this information.

## SUPERIOR WASH CYCLE CONTROL

With our Wash Program Manager software you can easily create custom wash programs on your PC.



### Compass Control

With Compass Control you choose the programs that best suit your needs. Modify standard wash programs to find the perfect balance between low water and energy consumption while optimizing wash results and processing time. You can also create your own programs. Multilingual.



Call today for information on the full line of Wascomat washers, dryers, flatwork ironers and low-cost financing and leasing.

**Wascomat** Laundry Equipment

1-800-645-2204 • www.wascomat.com

461 Doughty Blvd., Inwood, NY 11096-0338

Sales and Administration – Tel: 516-371-4400 • Fax: 516-371-4204 • e-mail: sales@wascomat.com

Spare Parts – Tel: 516-371-2000 • Fax: 516-371-4029 • e-mail: parts@wascomat.com

Technical Support – Tel: 516-371-0700 • Fax: 516-371-4029 • e-mail: service@wascomat.com

En Mexico: Llame gratis a este numero 001-800-010-1010

Your local independent authorized dealer

